



## | Product Description |

3-Parallel Ports 10/100Mbps Ethernet Print Server

# - PAN3001 -

3-Parallel Ports Print Server

Version : 1.1.3

2014 - 7 - 1

Generic Model Name : **PAN3001**

### Interfaces

<b>Parallel</b> : 3 DB-25-pin female Centronic port, supporting bi-directional communication
<b>LAN</b> : Compliant with IEEE 802.3/802.3u standard, 10/100Mbps auto-sensing, RJ-45 (UTP) connector

### Key Software Specification

<b>Easy-to-Use Windows Setup Wizard</b>	Yes (Windows-based Setup CD)
<b>Network Operating System Support</b>	Windows 9x/Me/NT4.0/2000/XP/Vista/7/8/10 Mac OS 8.1 or higher, UNIX/Linux NetWare (Bindery/NDS)
<b>Network Protocol Support*</b>	TCP/IP, IPX, NetBEUI, AppleTalk, LPR, SMB over IP*, RAW TCP9100
<b>Internet Printing Protocol (IPP) Support</b>	Yes
<b>Windows Print Monitor Technology</b>	Yes
<b>DHCP (client) Support</b>	Yes
<b>Default IP Address</b>	192.168.0.10; DHCP: off
<b>Print Job Log</b>	Yes
<b>Management</b>	1. Web interface 2. Windows-based Setup Program
<b>Software Upgradeable</b>	1. Web interface 2. Windows-based Setup Program 3. TFTP
<b>SNMP &amp; HP Web JetAdmin Support</b>	Yes

\* As of the release of this specification. The specification is subject to change without prior notice.

## Hardware Specification

CPU	High-performance RISC-cored SoC processor
Flash	1Mbytes
System Memory	2Mbytes SDRAM
Parallel Port	3 DB-25-pin female Centronic port, supporting bi-directional communication
LAN Port	10/100Mbps, auto-sensing, RJ-45(UTP) connector
Reset Button	Yes

LED	Position	Type	Color	Specification
Power	Side	SMT	Uni-color, Red	a. When the power is supplied OK, it goes on. b. When no power or power supply is NOT OK, it goes off.
Status	Top	SMT	Uni-color, Green	a. When powered on, it flashes for the P.O.S.T. b. When in Upgrade Mode, it flashes slowly. c. When being upgraded, it flashes quickly.
LAN Link	Side	SMT	Uni-color, Green	a. When the cable (Link) is OK, it goes on. b. If the cable (Link) is NOT OK, it goes off.

## Others

Dimension	228 (Length) x 137 (Width) x 36(Height) mm
Power Supply	5V, 2A
Weight	307~320g (Device Only)
EMI Certifications	CE / FCC Class B
Temperature Operating	0 ~ 50°C; Storage : -5 ~ 65 °C
Humidity Operating	0 ~ 70%; Storage : 0 ~ 80%

\* As of the release of this specification. The specification is subject to change without prior notice.

## Housing

